

Dry Cargo Tape HD - Hatch Sealing Tape

Specially designed tape to help prevent water damage to cargo

Composition

Dry Cargo Tape HD - Hatch Sealing Tape is comprised of a synthetic fibre fabric impregnated and coated with a polymer modified bitumen adhesive. The outer surface of the tape has a high density polyethylene backing. The adhesive layer is protected prior to use by a release film which is discarded during application.

Uses

Dry Cargo Tape HD - Hatch Sealing Tape is specially designed for sealing metal hatch covers on cargo ships to prevent water entering at poorly mating joints with consequent damage to cargo. The thick adhesive conforms to typical metal deck surfaces.

Service Temperature: -20°C to 65°C

Characteristics

Dry Cargo Tape HD - Hatch Sealing Tape:

- conforms to typical metal deck surfaces,
- provides excellent resistance to water, acids, alkali and salts,
- adheres to steel, brass, aluminium, rigid plastics, glass and sound paint finishes, and
- helps prevent water damage to cargo.

Typical Properties

| | |
|---------------------|-----------------------|
| Weight | 2.8 kg/m ² |
| Thickness | 2.7 mm |
| Breaking strength | 350 N/50mm |
| Elongation at break | 22% |
| Peel strength | |
| <i>To steel</i> | 3 N/mm |
| <i>To self</i> | 3 N/mm |

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

Page 1 of 1
Revision date: 26/01/2018

Winn & Coales (Denso) Ltd
Denso House, Chapel Road,
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511
Fax: +44 (0) 20 8761 2456
Email: mail@denso.net Web: www.denso.net